



Wizzard Repair Products

Wood • Marine • Metal • Auto-RV • Stucco-Masonry

SOP# 88 06-17-16

Wizzard Repair Products- Instructions for Use

Step 1 Repair Site

Remove loose deteriorated base material (wood, fiberglass, rusted metal) from the repair sight.



Step 2 Clean Restoration Area

Spray repair site with Biocide cleaner to treat and/or prevent mold. Mold is a food source for Fungus.



WizzardRepairProducts.com 

P.O Box 7207, Capistrano Beach CA 92624 | (888) 247-4052 | info@wizzardrepairproducts.com



Wizzard Repair Products

Wood • Marine • Metal • Auto-RV • Stucco-Masonry

SOP# 88

Wizzard Repair Products- Instructions for Use

Step 3 Treat Fungus

Spray repair sight with Fungicide to treat and/or prevent Fungus. Fungus eats wood fibers.



Step 4 Install Copper / Borate Rods

Drill holes in wood applications approximately ¼ inch deeper than borate/copper rod length, and install to prevent future infestation.



WizzardRepairProducts.com 

P.O Box 7207, Capistrano Beach CA 92624 | (888) 247-4052 | info@wizzardrepairproducts.com



Wizzard Repair Products

Wood • Marine • Metal • Auto-RV • Stucco-Masonry

SOP# 88

Wizzard Repair Products- Instructions for Use

Step 5 Liquid Epoxy

Mix equal parts of the epoxy liquid A & B together and coat the repair sight to fortify wood and provide the bond bond in repair site, 30 minutes or less.



Step 6 Epoxy Dough

1. Mix equal parts of white and brown epoxy dough together until they blend to a tan color.
2. Pack blended epoxy dough into repair sites, and on top of the borate/copper rods. Dough should be site flush to above adjacent surfaces.
3. Trim off excess epoxy above repair surface within 10 minutes of applying



WizzardRepairProducts.com 

P.O Box 7207, Capistrano Beach CA 92624 | (888) 247-4052 | info@wizzardrepairproducts.com



Wizzard Repair Products

Wood • Marine • Metal • Auto-RV • Stucco-Masonry

SOP# 88

Wizzard Repair Products- Instructions for Use

Step 7 Topping Compound

Mix Topping Compound with ground wood to a consistency of cake frosting or thick oatmeal, and apply over repair sight to create a smooth transition to surrounding surfaces. The topping compound/wood fiber provide a surface which will except stain.



Step 8 Final Step

Stain or prime and paint repair sight.



THANK YOU FOR YOUR INTEREST IN WIZZARD REPAIR PRODUCTS

WizzardRepairProducts.com 

P.O Box 7207, Capistrano Beach CA 92624 | (888) 247-4052 | info@wizzardrepairproducts.com